

## PRODUCT SAFETY DATA SHEET

This generic SDS is provided by MGS Ltd to give information to assist with material handling of the products listed.

SDS No: HS8 C42-038  
Version: MGS 1/JS  
Date: February 2018  
Review Date: July 2020

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier Substance Name:

Name: Post Mix

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against: Uses: Refer to relevant Technical Data Sheet Uses advised against: Refer to relevant Technical Data Sheet

#### 1.3. Company identification Name:

Name:	MGS Ltd
Address:	Rougham Ind Est, Bury St Edmunds, IP30 9ND
Country:	UK
Phone N°:	+44 01359 271167
Fax N°:	+44 01359 271168
E-mail:	sales@mgs.co.uk

#### 1.4 Emergency Telephone Number

Emergency telephone at the company	+44 7738 197 517
Available outside office hours:	Yes
Language of the phone service:	English
E-mail of competent person responsible	darren.portway@mgs.co.uk
National contact:	Darren Portway

### SECTION 2: HAZARDS IDENTIFICATION

Irritating to eyes and skin. Risk of serious damage to eyes. May cause burns in the presence of moisture due to generation of strong alkaline solution of calcium hydroxide. May cause allergic dermatitis due to the sensitivity of an individual's skin to soluble chromium (VI) in the presence of moisture. Dust may cause irritation of the respiratory tract.

#### 2.1 Classification of the substance or mixture:

##### 2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP):

Hazard Class	Hazard Category	Classification Procedure
Skin irritation	2	On the basis of test data
Serious eye damage/eye irritation	1	On the basis of test data
Skin sensitization	1	On the basis of literature survey
Specific target organ toxicity single exposure respiratory tract irritation	3	On the basis of literature survey

## PRODUCT SAFETY DATA SHEET

This generic SDS is provided by MGS Ltd to give information to assist with material handling of the products listed.

SDS No: HS8 C42-038  
Version: MGS 1/JS  
Date: February 2018  
Review Date: July 2020

### 2.1.2 Classification according to Directive (EC) 1272/2008 Irritant/Corrosive

## 2.2 Label elements

### 2.2.1 Labelling according to Regulation (EC) 1272/2008(CLP): Signal word:

Danger

Hazard pictogram:



Hazard statements:

H318: Causes serious eye damage  
H315: Causes skin irritation  
H317: May cause an allergic skin reaction  
H335: May cause respiratory irritation

Precautionary statements:

P102: Keep out of reach of children  
P280: Wear protective gloves/protective clothing/eye protection/face protection P305+P351+P338+P310: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE or doctor/physician.  
P302+P352+P333+P313: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.  
P261+P304+P340+P312: Avoid breathing dust/fumes, gas, mist, vapors, spray.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician.  
P501: Dispose of contents/container according to local regulations. Supplemental information:  
Skin contact with wet mortar may cause irritation, dermatitis or burns.  
May cause damage to products made of aluminum or other non-noble metals.

## PRODUCT SAFETY DATA SHEET

This generic SDS is provided by MGS Ltd to give information to assist with material handling of the products listed.



SDS No: HS8 C42-038  
Version: MGS 1/JS  
Date: February 2018  
Review Date: July 2020

### 2.2.2 Labelling according to Directive (EC)1272/2008:

#### 2.2 Label elements

##### Irritant

##### Risk phrases:

**H335/H317** Irritating to respiratory system and skin

**H318** Risk of serious damage to eyes

**H315** May cause sensitization by skin contact

##### Safety phrases:

**S2** Keep out of reach of children **S22** Do not breathe dust

**S24/25** Avoid contact with skin and eyes

**S26** In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

**S36/37/39** Wear suitable protective clothing, gloves and eye/face protection

**S46** If swallowed, seek medical advice immediately and show this container or label

#### 2.3 Other hazards

Long term exposure to dust can lead to the development of lung disease during mechanical cutting, grinding or sanding of the set product.

## SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

#### 3.1 Mixtures:

The principal constituents of this product include Calcium and Ferro Silicates, Ferro Sulphates and Aluminates along with small amounts of Alkalis, Lime, and Chlorides together with trace amounts of Chromium Compound. Hazardous Ingredient- Calcium Hydroxide generated on contact with water. Hexavalent chromium salts dissolve in water.

## PRODUCT SAFETY DATA SHEET

This generic SDS is provided by MGS Ltd to give information to assist with material handling of the products listed.

SDS No: HS8 C42-038  
Version: MGS 1/JS  
Date: February 2018  
Review Date: July 2020

### Under CLP EC 1272/2008

Ingredient	%	Reach Reg No.	CAS No.	EC No.	CLP Hazard Category	Hazard Statements
Portland Cement (CEM 1)	5-30	N/a	6599715-1	266043-4	(1) STOT SE 3 (2) Skin irritation 2 (3) Serious eye damage/ eye irritation 1 (4) Skin sensitization 1	(1) H335 – May cause respiratory irritation. (2) H315 – Causes skin irritation (3) H318 – Causes serious eye damage (4) H317 – May cause an allergic skin reaction

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures:

#### 4.1.1 Routes of exposure;

<b>Skin contact</b>	Remove affected clothing, footwear, watches, jewellery etc. Wash skin with soap and water immediately. Wash contaminated clothing before re-use. Seek medical attention if irritation occurs
<b>Ingestion</b>	Immediately rinse mouth and drink plenty of water. Do not induce vomiting. Seek immediate medical advice if person becomes uncomfortable. Show the container or label used
<b>Inhalation (dust)</b>	Move to fresh air. Dust in throat and nasal passages should clear spontaneously. Seek medical attention if irritation persists or later develops or if discomfort, coughing or other symptoms persist
<b>Eye contact</b>	<b>Speed is essential.</b> Immediately wash eyes with plenty of eyewash solution or running water, holding eyelids apart for 15 minutes. Do not rub eyes in order to avoid possible cornea damage as a result of mechanical stress. Always seek further specialist medical/eye specialist attention to check that all particles have been removed

## PRODUCT SAFETY DATA SHEET

This generic SDS is provided by MGS Ltd to give information to assist with material handling of the products listed.



SDS No: HS8 C42-038  
Version: MGS 1/JS  
Date: February 2018  
Review Date: July 2020

### 4.2 Most important symptoms and effects, both acute and delayed;

#### **Eyes:**

Eye contact with mortar (dry or wet) may cause serious and potentially irreversible injuries.

#### **Skin:**

Product may have an irritating effect on moist skin (due to sweat or humidity) after prolonged contact or may cause contact dermatitis after repeated contact. Prolonged skin contact with wet mortar or concrete may cause serious burns because they develop without pain being felt (for example when kneeling in wet product even when wearing trousers).

#### **Inhalation:**

Irritating to the respiratory tract in high concentration. Environment: Under normal use, this product is not hazardous to the environment.

### 4.3 Indication of any immediate medical attention and special treatment needed;

When contacting further medical advice. Show container, label or this SDS sheet.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1 Extinguishing media:

#### 5.1.2 Suitable extinguishing media;

The product is not combustible. Use a dry powder, foam or CO2 fire extinguisher to extinguish the surrounding fire. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### 5.1.3 Unsuitable extinguishing media; None identified.

### 5.2 Special hazards arising from the substance or mixture:

None identified

### 5.3 Advice for fire fighters:

None identified

## PRODUCT SAFETY DATA SHEET

This generic SDS is provided by MGS Ltd to give information to assist with material handling of the products listed.



SDS No: HS8 C42-038  
Version: MGS 1/JS  
Date: February 2018  
Review Date: July 2020

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures:

- 6.1.1. For Non-emergency personnel;  
Wear suitable protective equipment (see section 8).
- 6.1.2. For emergency responders; N/a

#### 6.2. Environmental precautions:

Do not wash product down sewage and drainage systems or into bodies of water (e.g. streams).

#### 6.3. Methods and material for containment and cleaning up:

##### Dry product:

Use cleanup methods such as vacuum cleaning-up or vacuum extraction fitted with EPA/HEPA air filters which do not cause airborne dispersion. Never use compressed air. Alternatively, wipe-up the dust by mopping, wet brushing or by using water spray or hoses (fine mist to avoid dust becoming airborne) and remove slurry.

If not possible, remove by slurring with water (see wet product).

If only dry cleaning by brushing can be done, ensure all appropriate personnel wear correct PPE including dust mask and eye protection at all times (see section 8).

Avoid inhalation of dust and place in a container and dispose of as detailed in section 13.

##### Wet product:

Clean up wet material and place in container or controlled location. Allow material to dry and solidify before disposal as detailed in section 13.

#### 6.4. Reference to other sections:

For more information on exposure controls/personal protection or disposal considerations, please check section 8 and 13.

### SECTION 7: HANDLING AND STORAGE

#### 7.1. Precautions for safe handling:

- 7.1.1. Protective Measures;  
Do not ingest. Avoid contact with skin. Avoid contact with eyes.  
Wear protective equipment (refer to section 8 of this safety data sheet). Avoid generating dust.

## PRODUCT SAFETY DATA SHEET

This generic SDS is provided by MGS Ltd to give information to assist with material handling of the products listed.

SDS No: HS8 C42-038  
Version: MGS 1/JS  
Date: February 2018  
Review Date: July 2020

**7.1.2** Advice on general occupational hygiene;  
General occupational hygiene measures are required to ensure safe handling of the product. These measures involve good personal and housekeeping practices. Wash hands after use if contaminated. Avoid wearing contaminated clothing. Do not handle or store near food and beverages or smoking material. In dusty environment, wear dust mask, protective goggles and gloves.

### **7.2 Conditions for safe storage, including any incompatibilities:**

Bulk materials should be stored in silos that are waterproof. Packed products should be stored in unopened bags clear of the ground in cool, dry conditions and protected from excessive draught, excesses in temperatures in order to avoid degradation of quality.

Bags should be stacked in a stable manner.

Do not use aluminum containers due to incompatibility of the materials.

### **7.3 Specific end use(s):**

No additional information for the specific end users.

## SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

### **8.1 Control parameters:**

Workplace exposure limits:

The following Workplace Exposure Limits (WEL's) for airborne dust are given in HSE Guidance Note EH40:

Total dust -	W.E.L. 10mg/m <sup>3</sup>	8 Hrs T.W.A.
Respirable dust -	W.E.L. 4mg/m <sup>3</sup>	8 Hrs T.W.A.
Crystalline Silica -	W.E.L. 0.1mg/m <sup>3</sup>	8 Hrs T.W.A.

(Respirable)

W.E.L. = Workplace Exposure Limit

T.W.A. = Time Weighted Average

### **8.2 Exposure controls:**

**8.2.1** Appropriate engineering controls;  
Measures to reduce generation of dust and to avoid dust propagating in the environment such as regular housekeeping, exhaust ventilation and dry clean-up methods which do not cause airborne dispersion.




## PRODUCT SAFETY DATA SHEET

This generic SDS is provided by MGS Ltd to give information to assist with material handling of the products listed.



SDS No: HS8 C42-038  
Version: MGS 1/JS  
Date: February 2018  
Review Date: July 2020

### 8.2.2 : Individual protection measures, such as personal protective equipment:

<p>8.2.2.1: Eye/face protection</p>		<p>Wear approved glasses or goggles according to EN 166 with anti-mist for eye protection when handling wet or dry materials</p>
<p>8.2.2.2: Skin protection</p>		<p>Overalls and/or long-sleeved jackets and full-length trousers should be worn to protect skin from contact with wet products. Outer clothing should be waterproof if contact with wet product is likely. Wear impermeable boots to protect feet. Safety wellington boots should be worn if working with wet product, with waterproof trousers pulled over them to help prevent product entering the boots. If the product saturates clothing, or enters gloves or boots, remove the articles immediately and wash before wearing again</p>
<p>8.2.3.3: Respiratory protection</p>		<p>When a person is potentially exposed to dust levels above exposure limits, an appropriate respirator must be used dependent on expected dust levels</p>
<p>8.2.2.4: Thermal Hazards</p>		<p>The substance does not represent a thermal hazard, thus special consideration is not required</p>
<p>8.2.3: Environmental Exposure Control</p>		<p>Not relevant unless large volume of product enters the watercourse</p>



## PRODUCT SAFETY DATA SHEET

This generic SDS is provided by MGS Ltd to give information to assist with material handling of the products listed.



SDS No: HS8 C42-038  
Version: MGS 1/JS  
Date: February 2018  
Review Date: July 2020

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties:

Appearance:	<b>Wet Product</b> – semi solid state <b>Dry Product</b> – dry powder
Odour:	Slight, earthy odour
Odour threshold:	N/a
pH:	11-13.5, (20°C in water, water solid ratio 1:2)
Melting point:	1250 (typical)
Boiling point:	Not determined
Flash point:	N/a
Evaporation rate:	N/a
Flammability:	Non-flammable
Explosive limits:	Non-explosive
Vapour pressure:	N/a
Vapour density:	0 at 20°C
Relative density:	3.0 (typical)
Solubility in water:	Some components sparingly soluble Partition
coefficient:	N/a
Auto ignition temperature:	N/a
Decomposition temperature:	N/a Viscosity:
	N/
a	
Oxidizing properties:	No oxidizing properties

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

When mixed with water, will harden into a stable mass that is not reactive in normal environments.

#### 10.2 Chemical Stability:

Stable product under recommended storage and handling conditions.

#### 10.3 Possibility of hazardous reactions:

This product does not cause hazardous reactions.

#### 10.4 Conditions to avoid:

Dry Products – avoid humid conditions which may cause lump formation and loss of product quality.

## PRODUCT SAFETY DATA SHEET

This generic SDS is provided by MGS Ltd to give information to assist with material handling of the products listed.

SDS No: HS8 C42-038  
Version: MGS 1/JS  
Date: February 2018  
Review Date: July 2020

### 10.5 Incompatible Materials:

Acids, ammonium salts, aluminum or other non-noble metals. Uncontrolled use of aluminum powder in wet product should be avoided as hydrogen is produced.

### 10.6 Hazardous Decomposition Products:

This product does not decompose into any hazardous products.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

Toxicity Endpoints	Outcome of the effects assessment
Acute Toxicity	Based on available data, the classification criteria are not met
Skin corrosion/irritation	<b>Category 2</b> When in contact with wet skin may cause thickening, cracking or fissuring on the skin. Prolonged contact in combination with abrasion may cause severe burns
Serious eye damage/irritation	<b>Category 1</b> Direct contact may cause corneal damage by mechanical stress, immediate or delayed irritation or inflammation. Direct contact by large amounts may cause effects ranging from moderate irritation to chemical burns and blindness
Respiratory or skin sensitization	<b>Category 1</b> Some individuals may develop eczema upon exposure by either the high pH which induces irritant contact dermatitis after prolonged contact, or by an immunological reaction to soluble Cr(VI) which elicits allergic contact dermatitis. The response may appear in a variety of forms ranging from a mild rash to severe dermatitis. If the product contains a soluble Cr (VI) reducing agent and as long as the period of effectiveness of the agent is not exceeded, a sensitizing effect is not expected. There is no indication of sensitization of the respiratory system
Repeated dose toxicity	Based on available data, the classification criteria are not met
Germ cell mutagenicity	Based on available data, the classification criteria are not met

## PRODUCT SAFETY DATA SHEET

This generic SDS is provided by MGS Ltd to give information to assist with material handling of the products listed.

SDS No: HS8 C42-038  
Version: MGS 1/JS  
Date: February 2018  
Review Date: July 2020

Carcinogenicity	Based on available data, the classification criteria are not met
Toxicity for reproduction	Based on available data, the classification criteria are not met
STOT – single exposure	<b>Category 3</b> Dust exposure may irritate the throat and respiratory tract. Coughing, sneezing, and shortness of breath may occur following exposures in excess of occupational exposure limits
STOT – repeated exposure	There is an indication of Chronic Obstructive Pulmonary Disease. The effects are acute and due to high exposures. No chronic effects or effects at low concentrations have been observed
Aspiration hazard	Not applicable as these products are not used as an aerosol

### Information on likely routes of exposure:

Contact with skin, eyes, ingestion and dust inhalation.

### Symptoms relating to the physical, chemical and toxicological characteristics:

Dust exposure may irritate the throat and respiratory tract. Coughing, sneezing, and shortness of breath may occur following exposures in excess of occupational exposure limits. When in contact with wet skin may cause thickening, cracking or fissuring on the skin. Prolonged contact in combination with abrasion may cause severe burns. Some individuals may develop eczema upon exposure by either the high pH which induces irritant contact dermatitis after prolonged contact, or by an immunological reaction to soluble Cr(VI) which elicits allergic contact dermatitis

**Delayed and immediate effects as well as chronic effects from short and long-term exposure:** Delay in treating eye contact can lead to serious and permanent eye damage. Long term exposure to dust above the exposure limits can lead to lung disease.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity:

The product is not hazardous to the environment. The addition of large amounts of the product to water may however, cause a rise in pH and may, therefore, be toxic to aquatic life under certain circumstances.

### 12.2 Persistence and Degradability:

Not relevant as this product is an inorganic material. After hardening, it presents no toxicity risks.

## PRODUCT SAFETY DATA SHEET

This generic SDS is provided by MGS Ltd to give information to assist with material handling of the products listed.

SDS No: HS8 C42-038  
Version: MGS 1/JS  
Date: February 2018  
Review Date: July 2020

### 12.3 Bio accumulative potential:

Not relevant as this product is an inorganic material. After hardening, it presents no toxicity risks.

### 12.4 Mobility in Soils:

Not relevant as this product is an inorganic material. After hardening, it presents no toxicity risks.

### 12.5 Results of PBT and vPvB assessment:

Not relevant as this product is an inorganic material. After hardening, it presents no toxicity risks.

### 12.6 Other adverse effects:

No other adverse effects are identified.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods:

#### **Product – has exceeded its shelf life (indicated on packaging);**

(and when demonstrated that it contains more than 0.002% Cr (VI): shall not be used/ sold other than for use other than for use in controlled closed and totally automated processes or should be recycled or disposed of according to local legislation or treated again with reducing agent.

#### **Product – unused residue or dry spillage;**

Pick up dry unused residue or dry spillage as is (refer to Section 6). Mark up containers. Possibly reuse depending upon shelf life considerations and the requirements to avoid dust exposure. In case of disposal, harden with water and dispose according to section

6.3 above.

#### **Product – slurries;**

Allow to harden, avoid entry in sewerage and drainage systems or into bodies of water. Dispose of as hardened product as concrete waste. This is not classed as a dangerous waste. LoW/EWC entries; 16 03 04 - inorganic wastes containing no dangerous substances. 17 01 01 - construction and demolition wastes – concrete.

#### **Packaging;**

Completely empty and clean packaging and process in accordance with local legislation. LoW/EWC entry: 15 01 01 - waste paper and cardboard packaging 15 01 02 - plastic packaging If packaging is contaminated; 20 03 01 – mixed municipal waste

## PRODUCT SAFETY DATA SHEET

This generic SDS is provided by MGS Ltd to give information to assist with material handling of the products listed.

SDS No: HS8 C42-038  
Version: MGS 1/JS  
Date: February 2018  
Review Date: July 2020

### SECTION 14: TRANSPORT INFORMATION

These products are not classified as hazardous for transport. No special precautions are needed apart from those mentioned under Section 8.

- 14.1 UN number – not relevant
- 14.2 UN proper shipping name – not relevant
- 14.3 Transport hazard class(es) – not relevant
- 14.4 Packing group – not relevant
- 14.5 Environmental hazards - not relevant
- 14.6 Special precautions for user - not relevant
- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code - not relevant

### SECTION 15: REGULATORY INFORMATION

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance:

The product contains Ordinary Portland Cement which is a mixture that is not subject to registration according to REACH. Cement clinker is exempt from registration (Art2.7(b) and Annex V.10 of REACH).

Workplace Exposure Limits – HSE Guidance note EH40. Control of Substances Hazardous to Health latest Regulations.

The marketing and use of these products is subject to a restriction on the content of soluble Cr(VI) (REACH Annex XVII point 47 Chromium VI compounds).

#### 15.2 Chemical Safety Assessment:

A chemical safety assessment has not been carried out for this substance.

### SECTION 16: OTHER INFORMATION

#### 16.1 Hazard Statements:

H318: Causes serious eye damage H315: Causes skin irritation H317: May cause an allergic skin reaction

H335: May cause respiratory irritation

## PRODUCT SAFETY DATA SHEET

This generic SDS is provided by MGS Ltd to give information to assist with material handling of the products listed.

SDS No: HS8 C42-038  
Version: MGS 1/JS  
Date: February 2018  
Review Date: July 2020

### 16.2 Identified uses and use descriptors and categories

The table below gives an overview of all relevant identified uses of cement or cement containing hydraulic binders. All the uses have been grouped in these identified uses because of the specific conditions of exposure for human health and environment. For each specific use, a set of risk management measures or localised controls has been derived (see section 8) which need to be put in place by the user of cement or cement containing hydraulic binders to bring the exposure to an acceptable level.

Proc	Identified Used – Use Description	Manufacture / Formulation of	Professional/ Industrial use of
		Building and construction materials	
2	Use in closed, continuous process with occasional controlled exposure, eg industrial or professional manufacture of hydraulic binders	X	X
3	Use in closed batch process, eg industrial or professional manufacture of ready-mix concrete	X	X
5	Mixing or blending in batch process for formulation of mixtures and articles, eg industrial or professional manufacture of pre-cast concrete	X	X
7	Industrial spraying, eg industrial use of wet suspensions of hydraulic binders by spraying		X
8a	Transfer of substance or mixture from/to vessels/ large containers at non-dedicated facilities, eg use of cement in bags to prepare mortar		X
8b	Transfer of substance or mixture from/to vessels/ large containers a dedicated facility, eg filling of silos, trucks or barges at cement plants X	X	X
9	Transfer of substance or mixture into small containers, eg filling of cement bags in cement plants	X	X
10	Roller application or brushing, eg products to improve adherence between building surfaces and finishing products		X
11	Non-Industrial spraying, eg professional use of wet suspensions of hydraulic binders by spraying		X
13	Treatment of articles by dipping and pouring, eg covering of construction products with a layer to improve the performance of the product		X
14	Production of mixtures or articles by tableting, compression extrusion, palletization, eg production of floor tiling	X	X
19	Hand-mixing with intimate contact and only PPE available, eg mixture of wet hydraulic binder on a construction site		X
22	Potentially closed processing operations with minerals/metals at elevated temperature in industrial setting, eg production of bricks		X
26	Handling of solid inorganic substances at ambient temperature, eg mixture of wet hydraulic binders	X	X

## PRODUCT SAFETY DATA SHEET

This generic SDS is provided by MGS Ltd to give information to assist with material handling of the products listed.



SDS No: HS8 C42-038  
Version: MGS 1/JS  
Date: February 2018  
Review Date: July 2020

### 16.3 Abbreviations and acronyms

ACGIH	American Conference of Industrial Hygienists
ADR/RID	European Agreements on the transport of Dangerous goods by Road/Railway APF Assigned protection factor
CAS	Chemical Abstracts Service
CLP	Classification, labelling and packaging (Regulation (EC) No 1272/2008) COPD Chronic Obstructive Pulmonary Disease
DNEL	Derived no-effect level
EC50	Half maximal effective concentration ECHA European Chemicals Agency
EINECS	European Inventory of Existing Commercial Chemical Substances EPA Type of high efficiency air filter
ES	Exposure scenario
EWC	European Waste Catalogue
FF P	Filtering facepiece against particles (disposable) FM P Filtering mask against particles with filter cartridge GefStoffV G efahrstoffverordnung
HEPA	Type of high efficiency air filter H&S Health and Safety
IATA	International Air Transport Association
IMDG	International agreement on the Maritime transport of Dangerous Goods LC50 Median lethal dose
MEASE	Metals estimation and assessment of substance exposure,
EBRC	Consulting GmbH for Eurometaux, <a href="http://www.ebrc.de/industrial-chemicals-reach/projects-and-references/mease.php">http://www.ebrc.de/industrial-chemicals-reach/projects-and-references/mease.php</a>
MS	Member State
OELV	Occupational exposure limit value PBT Persistent, bio-accumulative and toxic PNEC Predicted no-effect concentration PROC Process category
RE	Repeated exposure
REACH	Registration, Evaluation and Authorisation of Chemicals RPE Respiratory protective equipment
SCOEL	Scientific Committee on Occupational Exposure Limit Values SDS Safety Data Sheet
SE	Single exposure
STP	Sewage treatment plant STOT Specific Target Organ Toxicity
TLV-TWA	Threshold Limit Value-Time-Weighted Average TRGS Technische Regeln für Gefahrstoffe
VLE-MP	Exposure limit value-weighted average in mg by cubic meter of air vPvB Very persistent, very bio-accumulative w/w Weight by weight WWTP Waste water treatment plant

## PRODUCT SAFETY DATA SHEET

This generic SDS is provided by MGS Ltd to give information to assist with material handling of the products listed.



SDS No: HS8 C42-038  
Version: MGS 1/JS  
Date: February 2018  
Review Date: July 2020

### 16.4 Key literature references and sources of data

- (1) Portland Cement Dust - Hazard assessment document EH75/7, UK Health and Safety Executive, 2006. Available from: <http://www.hse.gov.uk/pubns/web/portlandcement.pdf>.
- (2) Observations on the effects of skin irritation caused by cement, Kietzman et al, *Dermatosen*, 47, 5, 184-189 (1999).
- (3) European Commission's Scientific Committee on Toxicology, Ecotoxicology and the Environment (SCTEE) opinion of the risks to health from Cr (VI) in cement (European Commission, 2002). [http://ec.europa.eu/health/archive/ph\\_risk/committees/sct/documents/out158\\_en.pdf](http://ec.europa.eu/health/archive/ph_risk/committees/sct/documents/out158_en.pdf).
- (4) Epidemiological assessment of the occurrence of allergic dermatitis in workers in the construction industry related to the content of Cr (VI) in cement, NIOH, Page 11, 2003.
- (5) U.S. EPA, Short-term Methods for Estimating the Chronic Toxicity of Effluents and Receiving Waters to Freshwater Organisms, 3rd ed. EPA/600/7-91/002, Environmental Monitoring and Support Laboratory, U.S. EPA, Cincinnati, OH (1994a) and 4th ed. EPA-821-R-02-013, US EPA, office of water, Washington D.C. (2002).
- (6) U.S. EPA, Methods for Measuring the Acute Toxicity of Effluents and Receiving Waters to Freshwater and Marine Organisms, 4th ed. EPA/600/4-90/027F, Environmental Monitoring and Support Laboratory, U.S. EPA, Cincinnati, OH (1993) and 5th ed. EPA-821-R-02-012, US EPA, office of water, Washington D.C. (2002).
- (7) Environmental Impact of Construction and Repair Materials on Surface and Ground Waters. Summary of Methodology, Laboratory Results, and Model Development. NCHRP report 448, National Academy Press, Washington, D.C., 2001.
- (8) Final report Sediment Phase Toxicity Test Results with *Corophium volutator* for Portland clinker prepared for Norcem A.S. by AnalyCen Ecotox AS, 2007.
- (9) TNO report V8801/02, An acute (4-hour) inhalation toxicity study with Portland Cement Clinker CLP/GHS 03-2010-fine in rats, August 2010.
- (10) TNO report V8815/09, Evaluation of eye irritation potential of cement clinker G in vitro using the isolated chicken eye test, April 2010.
- (11) TNO report V8815/10, Evaluation of eye irritation potential of cement clinker W in vitro using the isolated chicken eye test, April 2010.
- (12) Investigation of the cytotoxic and proinflammatory effects of cement dusts in rat alveolar macrophages, Van Berlo et al, *Chem. Res. Toxicol.*, 2009 Sept; 22(9):1548-58.
- (13) Cytotoxicity and genotoxicity of cement dusts in A549 human epithelial lung cells in vitro; Gminski et al, Abstract DGPT conference Mainz, 2008.
- (14) Comments on a recommendation from the American Conference of governmental industrial Hygienists to change the threshold limit value for Portland cement, Patrick A. Hessel and John F. Gamble, EpiLung Consulting, June 2008.
- (15) Prospective monitoring of exposure and lung function among cement workers, Interim report of the study after the data collection of Phase I-II 2006-2010, Hilde Notø, Helge Kjuus, Marit Skogstad and Karl-Christian Nordby, National Institute of Occupational Health, Oslo, Norway, March 2010.
- (16) MEASE, Metals estimation and assessment of substance exposure, EBRC Consulting GmbH for Eurometaux, <http://www.ebrc.de/industrial-chemicals-reach/projects-and-references/mease.php>.
- (17) Occurrence of allergic contact dermatitis caused by chromium in cement. A review of epidemiological investigations, Kåre Lenvik, Helge Kjuus, NIOH, Oslo, December 2011.



## PRODUCT SAFETY DATA SHEET

This generic SDS is provided by MGS Ltd to give information to assist with material handling of the products listed.

SDS No: HS8 C42-038  
Version: MGS 1/JS  
Date: February 2018  
Review Date: July 2020

### 16.5 Relevant H-Statements H318:

H318: Causes serious eye damage H315: Causes skin irritation H317: May cause an allergic skin reaction H335: May cause respiratory irritation

### 16.6 Training advice

In addition to health, safety and environmental training programs for their workers, companies must ensure that workers read, understand and apply the requirements of this SDS.

### 16.7 Further information

The data and test methods used for the purpose of classification of Common cements are given or referred to in section 11.1.

### 16.8 Revision:

Version Number:2

Date Prepared: 07/06/17 Supersedes; v1

Nature of Revision - This version produced in reference to Annex II of the REACH Regulation (EC) 1907/2006 as amended by Regulation 453/2010.

Removed all examples of "DPD 1999/45/EC" in favor of "(EC)1272/2008"

### 16.9 Disclaimer

The information on this data sheet reflects the currently available knowledge and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product, including the use of the product in combination with any other product or any other process, is the responsibility of the user. It is implicit that the user is responsible for determining appropriate safety measures and for applying the legislation covering his/her own activities.

The advice shown on this sheet is given as a guide to good practice but Marton Geotechnical Services Ltd can accept no responsibility for any loss, damage or injury howsoever caused in following it.

This version of the SDS supersedes all previous versions.

**End of safety data sheet**

## **PRODUCT SAFETY DATA SHEET**

This generic SDS is provided by MGS Ltd to give information to assist with material handling of the products listed.



**SDS No: HS8 C42-038**  
**Version: MGS 1/JS**  
**Date: February 2018**  
**Review Date: July 2020**